

**DESCRIPTION**

BATIFLEX AV 135 CARPET is a fireproofed plasticized floor covering printed with a carpet pattern and bonded onto a laminate backing

**PHYSICAL PROPERTIES**

Emboss			Carpet
Thickness		mm	1.50 ± 0.15
		mils	59 ± 6
Weight		g/m <sup>2</sup>	1750 ± 150
		oz/sq.yd	52 ± 4
Roll width		m	1.5 (-0 +10 mm)
		inch	59 (-0 + 0.4)
Roll length		lm	12 - 30
		lyd	13 lyd 4 " to 32 lyd 29 "

**PERFORMANCE**

<b>Fire resistance</b>	<b>FAR 25.853(a) App F Part I</b>		<b>conform</b>
Tensile strength	ISO 527/3		
	Longitudinal	daN/cm	≥ 60
	Transverse	daN/cm	≥ 55
Dimensional stability	NF EN 434 ASTM D 1204 Skrinkage after 24 hours at 70°C		≤ 0.1 %
Abrasion resistance	TABER ISO 9352	mg	250 ± 50
Color and light fastness	NF T 51055 / 51058 ISO 105B01 / 105B02 ISO 877		≥ 6
Resistance to chemicals	EN 423	-	Unaffected by diluted acids and bases Unaffected by domestic products (excluding solvents for plasticized PVC)
Hot welding	-	-	Yes
Impermeability	-	-	Yes